

USPA Electronic Bidet series: October 2013



**UB-6210 , 6235
6035R SERIES**

**UB-7000, 7235, 7035R
SERIES**

*For your next generation,
the standard of personal hygiene*

UB-6210, UB-6235 SERIES

Rear wash	The wash alternates between a gentle spray and a forceful spray for a thorough wash
Feminine wash	Provides gentle, smooth aerated water stream
Nozzle position adjustment	Nozzle's position can be adjusted forward and backward.
Water pressure adjustment	The water pressure of the spray can be adjusted
Pulsating (Massage)	Serves massage stream of water
Heated seat	Warms the toilet seat
Warm air dryer	Dries the wet areas with warm air
Temperature adjustment	The temperatures of the water, toilet seat and dryer can be adjusted
Deodorizer	Removes odor from the toilet bowl
Vertical two nozzles	Two nozzles provide separate rear wash and feminine wash
Occupied seat sensor	Unless seat is occupied, unit could not operate properly for user's safety
Self cleaning	Before and flushing, the nozzles tip are automatically cleaned.
Power saving	Power saving keeps energy cost effectively
Splash Guard	Specially designed splash guard prevents water splashing during use
Easy detachable	Newly designed mounting plate enables easy installation.
Certification	UL, UPC, CE, CB, PSE

UB-6035R SERIES

Rear wash	The wash alternates between a gentle spray and a forceful spray for a thorough wash
Feminine wash	Provides gentle, smooth aerated water stream
Nozzle position adjustment	Nozzle's position can be adjusted forward and backward.
Water pressure adjustment	The water pressure of the spray can be adjusted
Pulsating (Massage)	Serves massage stream of water
Heated seat	Warms the toilet seat
Warm air dryer	Dries the wet areas with warm air
Temperature adjustment	The temperatures of the water, toilet seat and dryer can be adjusted
Deodorizer	Removes odor from the toilet bowl
Remote control	Allows for easy operation while seated
Vertical two nozzles	Two nozzles provide separate rear wash and feminine wash
Occupied seat sensor	Unless seat is occupied, unit could not operate properly for user's safety
Self cleaning	Before and flushing, the nozzles tip are automatically cleaned.
Power saving	Power saving keeps energy cost effectively
Splash Guard	Specially designed splash guard prevents water splashing during use
Easy detachable	Newly designed mounting plate enables easy installation.
Certification	UL, UPC, CE, CB, PSE

In detail



	UB-6120	UB-6235	UB-6035R
Rear wash	●	●	●
Feminine wash	●	●	●
Heated seat	●	●	●
Warm water wash	●	●	●
Nozzle position control	●	●	●
Two nozzles	●	●	●
Pulsating (Massage)	●	●	●
Warm air dryer		●	●
Deodorizer		●	●
Self cleaning	●	●	●
Power saving	●	●	●
Remote Control			●
Splash Guard	●	●	●
Size (Round front, Elongated)	E / R	E / R	E / R
Occupied seat sensor	●	●	●
Certification	UL / UPC / CE / CB / PSE	UL / UPC / CE / CB / PSE	UL / UPC / CE / CB / PSE

Soft start, Screen filter, Soft closing, Easy installing and removal are applied to all models listed above

Function



Rear & Feminine wash



Kids



Built in air-pump



Easy to removal



Circuit breaker



Self cleaning



Heated seat



Power saving



Splash guard



Remote control
(Only for 6035R)



Soft start wash



Occupied seat sensor



Self diagnosis



Continuous water heating



11 safety devices



Nozzle position adjustment



Warm air dryer



Self cleaning



Ultra sonic soldering water-proof system



Two nozzles



Deodorizer
(UB-6235, UB-6035R
UB-7235 Only)



Soft closing



Easy detachable

Specifications

•Specifications could be changed without notice for user's convenience.
 •Recommended water supply pressure is between 14psi ~ 100psi (0.09mPa ~ 0.68mPa).

Kaizen Solutions EU Limited

	UB-6210	UB-6235	UB-6035R
Power rating	AC220V~240V, 50~60Hz, 1,160W	AC220V~240V, 50~60Hz, 1,160W	AC220V~240V, 50~60Hz, 1,160W
Power cord	1.8m	1.8m	1.8m
Cleansing	Rear wash : 900 ± 100ml / min. Feminine wash : 900 ± 100ml / min. Tank capacity : 800ml Water temperature : Room temp. ~ 104°F(40℃) Heater capacity : 1,100W Safety features : Thermal cut-off, Thermostat (bi-metal), Floating switch	Rear wash : 900 ± 100ml / min. Feminine wash : 900 ± 100ml / min. Tank capacity : 800ml Water temperature : Room temp. ~ 104°F(40℃) Heater capacity : 1,100W Safety features : Thermal cut-off, Thermostat (bi-metal), Floating switch	Rear wash : 900 ± 100ml / min. Feminine wash : 900 ± 100ml / min. Tank capacity : 800ml Water temperature : Room temp. ~ 104°F(40℃) Heater capacity : 1,100W Safety features : Thermal cut-off, Thermostat (bi-metal), Floating switch
Dryer	No	Air temperature : Room temp. ~ 140°F(60℃) Heater capacity : 280W Safety devices : Thermal cut-off, bi-metal	Air temperature : Room temp. ~ 140°F(60℃) Heater capacity : 280W Safety devices : Thermal cut-off, bi-metal
Heated seat	Seat temperature : Room temp. ~ 104°F(40℃) Heater capacity : 55W (230V) Safety devices : Thermal cut-off	Seat temperature : Room temp. ~ 104°F(40℃) Heater capacity : 55W (230V) Safety devices : Thermal cut-off	Seat temperature : Room temp. ~ 104°F(40℃) Heater capacity : 55W (230V) Safety devices : Thermal cut-off
Air Deodorizer	No	Catalytic filter	Catalytic filter
Remote control	No	No	Infrared remote control
Water supply pressure	11~107PSI (0.08~0.74MPa)	11~107PSI (0.08~0.74MPa)	11~107PSI (0.08~0.74MPa)
Circuit breaker	Within 15mA / 0.1 second	Within 15mA / 0.1 second	Within 15mA / 0.1 second
Net weight	10.3lb (4.7kg)	10.3lb (4.7kg)	10.3lb (4.7kg)
Size (Round front, Elongated)	R(466 x 500) / E(466 x 520)	R(466 x 500) / E(466 x 520)	R(466 x 500) / E(466 x 520)
Certification	UL, CE, CB, PSE	UL, CE, CB, PSE	UL, CE, CB, PSE



*UB-6210 , 6235, 6035R
SERIES*

***UB-7000, 7235,
7035R SERIES***

*For your next generation,
the standard of personal hygiene*

UB-7000, UB-7235 SERIES













Rear wash	The wash alternates between a gentle spray and a forceful spray for a thorough wash
Feminine wash	Provides gentle, smooth aerated water stream
Nozzle position adjustment	Nozzle's position can be adjusted forward and backward.
Water pressure adjustment	The water pressure of the spray can be adjusted
Pulsating (Massage)	Serves massage stream of water
Heated seat	Warms the toilet seat
Warm air dryer	Dries the wet areas with warm air
Temperature adjustment	The temperatures of the water, toilet seat and dryer can be adjusted
Deodorizer	Removes odor from the toilet bowl
Vertical two nozzles	Two nozzles provide separate rear wash and feminine wash
Occupied seat sensor	Unless seat is occupied, unit could not operate properly for user's safety
Self cleaning	Before and flushing, the nozzles tip are automatically cleaned.
Power saving	Power saving keeps energy cost effectively
Splash Guard	Specially designed splash guard prevents water splashing during use
Easy detachable	Newly designed mounting plate enables easy installation.
Certification	CE, CB, KIWA, WRAS

UB-7035 R_ remote control



Rear wash	The wash alternates between a gentle spray and a forceful spray for a thorough wash
Feminine wash	Provides gentle, smooth aerated water stream
Nozzle position adjustment	Nozzle's position can be adjusted forward and backward.
Water pressure adjustment	The water pressure of the spray can be adjusted
Pulsating (Massage)	Serves massage stream of water
Heated seat	Warms the toilet seat
Warm air dryer	Dries the wet areas with warm air
Temperature adjustment	The temperatures of the water, toilet seat and dryer can be adjusted
Deodorizer	Removes odor from the toilet bowl
Remote control	Allows for easy operation while seated
Vertical two nozzles	Two nozzles provide separate rear wash and feminine wash
Occupied seat sensor	Unless seat is occupied, unit could not operate properly for user's safety
Self cleaning	Before and flushing, the nozzles tip are automatically cleaned.
Power saving	Power saving keeps energy cost effectively
Splash Guard	Specially designed splash guard prevents water splashing during use
Easy detachable	Newly designed mounting plate enables easy installation.
Certification	CE, CB, KIWA, WRAS

Function

	Rear & Feminine wash		Kids		Built in air-pump		Easy to removal		Circuit breaker
	Self cleaning		Heated seat		Power saving		Splash guard		Remote control (Only for 6035R)
	Soft start wash		Occupied seat sensor		Self diagnosis		Continuous water heating		11 safety devices
	Nozzle position adjustment		Warm air dryer		Self cleaning		Ultra sonic soldering water-proof system		
	Two nozzles		Deodorizer (UB-6235, UB-6035R UB-7235 Only)		Soft closing		Easy detachable		



	UB-7000	UB-7235	UB-7035R
Rear wash	●	●	●
Feminine wash	●	●	●
Heated seat		●	●
Warm water wash	●	●	●
Nozzle position control	●	●	●
Two nozzles	●	●	●
Pulsating (Massage)		●	●
Warm air dryer		●	●
Deodorizer		●	●
Remote Control			●
Self cleaning	●	●	●
Power saving	●	●	●
Splash Guard	●	●	●
Size (Round front, Elongated)	E / R	E / R	E / R
Occupied seat sensor	●	●	●
Certification	CE, UL, KIWA, CB WRAS	CE, UL, KIWA, CB WRAS	CE, UL, KIWA, CB - SOON WRAS

Soft start, Screen filter, Soft closing, Easy installing and removal are applied to all models listed above

Specifications

- Specifications could be changed without notice for user's convenience.
- Recommended water supply pressure is between 14psi ~ 100psi (0.09mPa ~ 0.68mPa).

	UB-7000	UB-7235	UB-7035R
Power rating	AC220V~240V, 50~60Hz, 1,660W	AC220V~240V, 50~60Hz, 1,660W	AC220V~240V, 50~60Hz, 1,660W
Power cord	1.5m	1.5m	1.5m
Cleansing	Rear wash : 650 ± 100ml / min. Feminine wash : 650 ± 100ml / min. Tank capacity : 200ml Water temperature : Room temp. ~ 104°F(40℃) Heater capacity : 1,600W Safety features : Thermal cut-off, Thermostat (bi-metal), Floating switch	Rear wash : 650 ± 100ml / min. Feminine wash : 650 ± 100ml / min. Tank capacity : 200ml Water temperature : Room temp. ~ 104°F(40℃) Heater capacity : 1,600W Safety features : Thermal cut-off, Thermostat (bi-metal), Floating switch	Rear wash : 650 ± 100ml / min. Feminine wash : 650 ± 100ml / min. Tank capacity : 200ml Water temperature : Room temp. ~ 104°F(40℃) Heater capacity : 1,600W Safety features : Thermal cut-off, Thermostat (bi-metal), Floating switch
Dryer	No	Air temperature : Room temp. ~ 140°F(60℃) Heater capacity : 280W Safety devices : Thermal cut-off, bi-metal	Air temperature : Room temp. ~ 140°F(60℃) Heater capacity : 280W Safety devices : Thermal cut-off, bi-metal
Heated seat	No	Seat temperature : Room temp. ~ 104°F(40℃) Heater capacity : 55W Safety devices : Thermal cut-off	Seat temperature : Room temp. ~ 104°F(40℃) Heater capacity : 55W Safety devices : Thermal cut-off
Air Deodorizer	No	Catalytic filter	Catalytic filter
Water supply pressure	11~107PSI (0.08~0.74MPa)	11~107PSI (0.08~0.74MPa)	11~107PSI (0.08~0.74MPa)
Circuit breaker	Within 15mA / 0.03 second	Within 15mA / 0.03 second	Within 15mA / 0.03 second
Net weight	9.25lb (4.2kg)	9.7lb (4.4kg)	9.7lb (4.4kg)
Size (Round front, Elongated)	R(466 x 500) / E(466 x 520)	R(466 x 500) / E(466 x 520)	R(466 x 500) / E(466 x 520)
Certification	CE, UL, KIWA, CB. WRAS	CE, UL, KIWA, CB. WRAS	CE, UL, KIWA, CB - SOON WRAS

Kaizen Solutions EU Limited



Gade View Hall
Hemel Hempstead Road
Nr Berkhamsted
HP4 1QR
United Kingdom

Ph: 00 44 (0) 1442 843120
www.bidet-shower.co.uk